



Water Filter Cartridge Product List								
FUNCTION ON WATER	MODEL NO	NAME	PICTURE	APPLICATION	SIZE			
1. Sediment Cartridges	PMB (PMB102501)	Melt Blown Cartridge		 Pre-filter for DI and RO water filtration systems; Effective removal of sand, silt, rust, dirt and scale particles. 	Size: 5"/10"/20"/30"/40" Micron rate: 0.5/1/5/10/20/25/50 μm			
	PSW (PSW102501)	String Wound Cartridge		 Pre-filter for municipal and well water filtration systems; Effective removal of sand, silt, rust, dirt and scale particles. 	Size: 5"/10"/20"/30"/40" Micron rate: 0.5/1/5/10/20/25/50 μm			
	PPC (PMB102501)	Polyester Pleated Cartridge		 Long service life and contain no binders, adhesives or surfactant; Big surface area with great dirt holding capacity 	Size: 5"/10"/20"/30"/40" Micron rate: 0.5/1/5/10/20/25/50 μm			
2. Carbon cartridges	CTO (CTO10250W)	Carbon Block Cartridge		 POU and RO water filtration systems; Coconut shell carbon with great dirt holding capacity; Effective removal of chlorine, VOCs, odor, color, THMs, etc. 	Size: 5"/10"/20"			
	CTO+ (CTO+10250B)	Carbon Block + Cartridge	1	 POU and RO water filtration systems; Coconut shell carbon with great dirt holding capacity; Effective removal of chlorine, VOCs, odor, color, THMs, etc. Effective inhibit scale and corrosion 	Size: 5"/10"/20"			
	GAC (GAC10250E)	Granular Activated Carbon Cartrid ge		 POU and POE water filtration systems; Coconut shell carbon with great dirt holding capacity; Effective removal of chlorine, VOCs, odor, color, THMs, etc. 	Size: 10"/20"			

3.Membranes	UFM (UFM10250F)	Ultrafiltration Membrane		1.Remove up to 99% of Bacterias, Colloids and Impurities 2.Filtration accuracy: 0.01 micron	Size: 10"
	UFM (UFM18120S)		Ĩ		Size: 12"
	NFM (NFM1812-100)	Nanofiltration Membrane	Î	1.Salt Rejection Rate:NaCl 30%-50%, MgSO4>96% 2.Filtration accuracy: 0.001 micron	Flow rate: 100/150/200/400/600/1000 GPD
	ROM (ROM1812-50)	Reverse Osmosis Membrane	Î	1.Remove up to 99% of Heavy Metals, TDS, Bacteria, Arsenic, Chlorine, Cadmium, Pyrogens, Giardia, Viruses, Cyanide and more; 2.Filtration accuracy: 0.0001 micron	Flow rate: 50/75/100//200/400/600/1000 GPD
4.Media cartridges	SWC (SWC10250E)	Softening Cartridge		 POU and POE water filtration systems; NSF certified ion exchange resin; Antiscale, remove water hardness 	Size: 10"/20"
	GAC+ (GAC+10250C)	GAC/KDF Cartridge		 POU and POE water filtration systems; Coconut shell carbon with KDF 55; Effective removal of heavy metals, microorganisms, chlorine, lead, iron, VOCs, odor, color, THMs, etc. 	Size: 10"/20"
	DI (DI10251C)	Deionization (DI) Cartridge		1.Remove the remaining TDS from membrane- filtered water to create ultra-pure water; 2.High-capacity mixed bed nuclear grade deionization resin	Size: 10"/20"
	DIC (DIC10251C)	Color Indicator DI Cartridge		1.Remove the remaining TDS from membrane- filtered water to create ultra-pure water; 2.High-capacity mixed bed nuclear grade deionization resin; 3.Color Changes when exhausted.	Size: 10"/20"
	ASC (ASC10250C)	Anti-scale Cartridge		 POU and POE water filtration systems; FDA approved material; Prevent scale formation and corrosion 	Size: 10"/20"
	ASC+ (ASC+10250C)	Anti-scale/GAC Cartridge		 POU and POE water filtration systems; FDA approved material; Prevent scale formation and corrosion; Effective removal of chlorine, VOCs, odor, color, THMs, etc. 	Size: 10"/20"

5.Inline cartridges	ALK+	Inline ALK+ Cartridge	İ	 POU and RO water filtration systems; Alkalization pH: 8.5 ~ 9.5+; Anti-oxidability ORP -150 ~ -300mv; Release beneficial minerals; Improve odor and taste 	Size: 11"	
	DI (DI10201C)	Inline Deionization (DI) Cartridge		1.Remove the remaining TDS from membrane- filtered water to create ultra-pure water; 2.High-capacity mixed bed nuclear grade deionization resin	Size: 10"	
6.Special cartridges	ARC (ARC10250C)	Arsenic Removal Cartridge		 Municipal and well water filtration systems; FDA approved material; Reduce both Arsenic III & V to below 10 ppb 	Size: 10"/20"	
	FRC (FRC10250C)	Fluoride Removal Cartridge		 Municipal and well water filtration systems; FDA approved material; Reduce fluorides to below 0.2 ppm. 	Size: 10"/20"	
	NRC (FRC10250C)	Nitrate Removal Cartridge		 Municipal and well water filtration systems; FDA approved material; 95% Nitrate Reduction 	Size: 10"/20"	
	ORC (ORC10250C)	Organic Removal Cartridge		 Municipal and well water filtration systems; FDA approved material; Effective removal of tannins and harmful organic substances. 	Size: 10"/20"	
	IRC (IRC10250C)	Iron Removal Cartridge		 Municipal and well water filtration systems; FDA approved material; Effective removal of dissolved iron up to 3ppm. 	Size: 10"/20"	
Head Office Cipher Engineers Pvt Ltd Corporate Head Office # 114, First Floor, Square 5, Sector B-17, Islamabad, Pakistan - Email: info@CipherEngineers.com Tel: +92 21 34682018 - Mob: +92 3219009954						



Page 3 of 3